

# LusterBoard®



**cRU** US S2S

Length and width tolerances:  
±1/2"

Square tolerance:  
Diagonals within 1/8"

Fire test:  
ASTM E84: Class A

Bond test:  
Acyclic aging: Pass

Wind velocity:  
160+ mph

UL File number:  
E60612

**Painted aluminum bonded to both sides of a furniture grade exterior plywood core**



## Benefits

- LusterBoard features a light, rigid construction, for easier handling and installation.
- LusterBoard's colorfast surface is warranted not to fade, flake, or peel.
- Average outdoor life expectancy, when properly installed, is 5 to 7 years.
- Easy to fabricate with standard carpentry tools.

## Construction

- Hardwood core is composed of a premium, exterior furniture-grade plywood, featuring smooth, tight, sanded veneers for optimum surface flatness.
- Factory-baked, polyester painted aluminum surfaces cover both sides of the hardwood core, creating a smooth, glossy finish.
- Surface is protected during shipping with a protective plastic, peel-off masking.

## Recommended applications

LusterBoard panels are recommended for wall or fence mounted signage, billboards, post and panel signs, scoreboards and A-frame signs. As with all wood core sign panels, LusterBoard must be edge-sealed for outdoor use.

## Specifications

Sizes Available	Finished Faces	Colors	Sheet Weight
48" x 96" (1/4")	Good 2 sides	White*	40 lbs.
48" x 120" (1/4")	Good 2 sides	White*	50 lbs.
48" x 96" (1/2")	Good 2 sides	All 12 colors	58 lbs.
48" x 120" (1/2")	Good 2 sides	White*	73 lbs.

\*Colors available by special order, minimum 10 panels per color.

